

# LVT片材产品技术参数表

## Vinyl Tile Floor Technical information



| Description 规格                                                    | Standard 标准             | Unit 单位         | Result 结果                       |
|-------------------------------------------------------------------|-------------------------|-----------------|---------------------------------|
| Total thickness<br>厚度                                             | EN ISO 24346 (EN 428)   | mm              | 2.0 / 2.5 / 3.0                 |
| Wear layer thickness<br>耐磨层厚度                                     | EN ISO 24340 (EN 429)   | cm              | 0.2 / 0.3 / 0.5                 |
| Size<br>尺寸规格                                                      | EN ISO 24342 (EN 427)   | mm              | 450*900<br>600*600<br>1000*1000 |
| CLASSIFICATION 类别                                                 |                         |                 |                                 |
| Norm / Product specification<br>标准/产品规范                           | -                       | -               | EN ISO 10582(EN 649)            |
|                                                                   | ASTM F 1700             | -               | Class III Type B                |
| European classification<br>欧洲分类                                   | EN ISO 10874(EN 685)    | class           | 23 - 31                         |
| Fire rating<br>防火等级                                               | EN 13 501-1             | class           | Bfl-s1                          |
| Static Electrical Propensity<br>静电倾向                              | EN 1815                 | kV              | < 2                             |
| Slip Resistance Wet<br>防湿滑性                                       | DIN 51 130              | class           | R10                             |
| PERFORMANCE 性能                                                    |                         |                 |                                 |
| Wear resistance<br>耐磨性                                            | EN 660.2                | mm <sup>3</sup> | ≤2.0                            |
| Wear Group<br>磨损组                                                 | NF 189                  | group           | T                               |
| Impact sound insulation<br>冲击隔音                                   | EN ISO 717-2            | dB              | 4                               |
| Dimensional stability (norm)<br>尺寸稳定性(标准)                         | EN ISO 23999 (EN 434)   | %               | ≤ 0.25                          |
| Dimensional stability<br>(average measured value)<br>尺寸稳定性(平均测量值) | -                       | %               | ≤ 0.10                          |
| Residual indentation<br>残余压痕                                      | EN ISO 24343-1 (EN 433) | mm              | ≤ 0.10                          |
| Castor chair test<br>脚轮测试                                         | ISO 4918 (EN 425)       | -               | OK                              |
| Colour fastness<br>色牢度                                            | EN 20 105-B02           | degree          | ≥6                              |
| Chemical products resistance<br>耐化学物质稳定性                          | EN ISO 26987 (EN 423)   | class           | OK                              |

